

Water Gas Lug Type High Performance Triple Eccentric Butterfly Valve

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	

Water Gas Lug Type High Performance Triple Eccentric Butterfly Valve



Product Description

Specifications

Size DN50--DN2000

Normal Pressure PN10/PN16/PN25,150-300 Lb

Working Temperature -15c---425c

Suitable Medium Chemicals,air,water,steam,oil,

acids,salts,etc

Standards:

Design standard	API609, ANSI B16.34, JISB2064, GB T12238
Face to Face	ANSIB16.10,JIS B2002,DIN3202,ISO5752, BS 5155
Flange drilling	DIN2501 PN10/16, ANSI 125/150/300, BS4504, JIS10K
Top Flange	ISO5211
Test Inspection	API598

Material:

Body	Carbon Steel, Stainless Steel, Alloy Steel,Cr-Mo Steel
Disc	Carbon Steel, Stainless Steel,Alloy Steel,Cr-Mo Steel
Stem	Stainless steel,Cr-Mo Steel
Sealing ring	Stainless Steel+Flexible graphite
Packing	Flexible graphite, Teflon

Application:

Chemicals, air, water, steam, oil, acids, salts ect

Features:


1. Eccentric structure allows reduce friction with sealing ring and exrtended life
2. Full sealing, zero leakage
3. It can be installed both vertivally and horizontally
4. Easy mount and dismante, convenient for service




815W
830W



815L
830L




815W
830W



815W 对夹式
830W Wafer type



815L 凸耳式
830L Protruding ears type



815W 法兰式
830W Flange type

■ 美标815W系列 API 815W Series (H0长度可按用户要求加长)

公称口径 Nominal diameter		尺寸(mm) Dimensions									参考重量(kg) Consult wight	
In	mm	L	L1	H	H0	D	D1	D2	M	Z-d		
2	50	43	108	110	345	152	120.5	92	M16	4-19	9	20
3	80	48	114	125	380	190	152.5	127	M16	4-19	11	29
4	100	54	127	145	415	229	190.5	157	M16	8-19	13	33
5	125	57	140	165	455	254	216	186	M20	8-22	16	38
6	150	57	140	175	545	279	241.5	216	M20	8-22	26	74
8	200	64	152	210	645	343	298.5	270	M20	8-22	34	86
10	250	71	165	250	695	406	362	324	M24	12-25	51	142
12	300	81	178	285	830	483	432	381	M24	12-25	72	167
14	350	92	190	320	900	533	476	413	M27	12-29	106	218
16	400	102	216	355	980	597	540	470	M27	16-29	133	275
18	450	114	222	380	1030	635	578	533	M30	16-32	176	315
20	500	127	229	415	1110	699	635	584	M30	20-32	190	395
24	600	154	267	475	1305	813	749.5	692	M33	20-35	394	580
30	750	165	292	580	1525	985	914	857	M33	28-35	476	717
32	800	190	318	630	1585	1060	978	914	M39	28-41	618	880
36	900	203	330	680	1765	1168	1085	1022	M39	32-41	762	1042

注：以上对夹式、对夹凸耳式、法兰式三种，传动方式有手动、蜗轮、气动和电动。用户订货时说明。
Attention: Above three sorts such as wafer, wafer protruding ears, flange, driving mode such as manual, worm wheel, pneumatic, and electric, user should specify when ordered.

■ 美标815L系列 API 815L Series

公称通径 Nominal diameter		尺寸(mm) Dimensions							参考重量(kg) Consult wight	
In	mm	L	H	H0	D1	D2	M	Z-d		
6	150	57	175	545	241.5	216	M20	8-22	28	
8	200	64	210	615	298.5	270	M20	8-22	36	
10	250	71	250	695	362	324	M24	12-25	53	
12	300	81	285	830	432	381	M24	12-25	74	
14	350	92	320	900	476	413	M27	12-29	110	
16	400	102	355	980	540	470	M27	16-29	138	
18	450	114	380	1030	578	533	M30	16-32	180	
20	500	127	415	1110	635	584	M30	20-32	196	
24	600	154	475	1305	749.5	692	M33	20-35	400	
30	750	165	580	1525	914	857	M33	28-35	482	
36	900	203	680	1765	1085	1022	M39	32-41	488	

■ 美标830W系列 API 830W Series

公称通径 Nominal diameter		尺寸(mm) Dimensions									参考重量(kg) Consult wight	
In	mm	L	L1	H	H0	D	D1	D2	M	Z-d		
2	50	43	108	110	345	165	127	92	M18	8-19	9	20
3	80	48	114	125	380	210	168	127	M20	8-22	12	29
4	100	54	127	145	415	254	200	157	M20	8-22	13	35
5	125	59	140	165	455	279	235	186	M20	8-22	18	40
6	150	59	140	175	545	318	270	216	M20	12-22	28	81
8	200	73	150	210	645	381	330	270	M24	12-26	37	94
10	250	83	160	250	695	445	387	324	M27	16-29	56	158
12	300	92	178	285	830	521	451	381	M30	16-32	79	183
14	350	117	190	320	900	584	514	413	M30	20-32	116	239
16	400	133	216	355	980	648	571	470	M33	20-35	146	302
18	450	149	222	380	1030	711	628	533	M33	24-35	193	346
20	500	159	229	415	1110	775	686	584	M33	24-35	209	434
24	600	181	267	475	1305	914	813	692	M39	24-41	433	638
30	750	181	292	580	1525	1092	997	857	M45	28-49	523	788
36	900	203	330	680	1765	1270	1168	1022	M50	32-53	838	1146

■ 美标830L系列 API 830L Series

公称通径 Nominal diameter		尺寸(mm) Dimensions							参考重量(kg) Consult wight	
In	mm	L	H	H0	D1	D2	M	Z-d		
6	150	59	175	545	270	216	M20	8-22	29	
8	200	73	210	615	330	270	M20	8-22	38	
10	250	83	250	695	387	324	M24	12-25	58	
12	300	92	285	830	451	381	M24	12-25	81	
14	350	117	320	900	514	413	M27	12-29	119	
16	400	133	355	980	591	470	M27	16-29	149	
18	450	149	380	1030	628	533	M30	16-32	198	
20	500	159	415	1110	686	584	M30	20-32	215	
24	600	181	475	1305	813	692	M33	20-35	436	
30	750	181	580	1525	997	857	M33	28-35	528	
36	900	203	680	1765	1168	1022	M39	32-41	843	

注：以上对夹式、对夹凸耳式、法兰式三种，传动方式有手动、蜗轮、气动和电动。用户订货时说明。
Attention: Above three sorts such as wafer, wafer protruding ears, flange, driving mode such as manual, worm wheel, pneumatic, and electric, user should specify when ordered.

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	